

**T.D. TAICHEE**  
**TX-617M**



Engineering Information	技术参数	TX-617M
Drivers	单元组成	LF:1 x 15" Voice-coil:3" HF:1 x 1.4" Voice-coil:3"
Frequency(+/-3dB)	频率响应(+/-3dB)	40-18000Hz
Dispersion(-6dB)	覆盖角度(-6dB)	80° x 50°
Sensitivity(1m/1W)	灵敏度 ( 1m/1W )	101dB
maximum SPL	输出声压级	128dB continuous/134dB peak
Nominal Impedance	额定阻抗	8 Ohms
Rated Power	功率	500W AES / 2000W peak
Recommended AMP	推荐放大器功率	750W/8 Ohms
Crossover Frequency	分频点	1500Hz
Connectors	输入连接器	2 x Speakon NL4MP
Dimensions(H x W x D)	净尺寸(H x W x D)	690mm x (479,210)mm x 453mm
Packing Dimensions(H x W x D)	包装尺寸(H x W x D)	762mm x 578mm x 552mm
Net Weight(KG)	净重量 ( KG )	36
Gross Weight(KG)	包装总重量 ( KG )	41.5
Construction	结构特点	
Physical	箱体外形	多角度型
Enclosure Material	箱体材料	桦木夹板
Enclosure Material	箱体面网	模压钢制圆形孔网面, 外加黑色海棉
Finish	表面漆	紫色环保水性耐磨油漆涂装 ( 可按客户要求定制颜色 )
Handing Position	吊装点	17个M10螺丝吊装孔位
Pole Mount	支撑座	底部 φ 35毫米支撑座
Caster	运输轮	
Applications	适用范围	礼堂, 会议室, 音乐酒吧, DISCO酒吧, KTV房间
Construction Drawing	结构示意图	

